Longopac Features & Certifications





LONGOPAC MINI

Diameter: 357 mm Standard: 60 meters long Strong: 45 meters long X-Strong: 35 meters long Super Strong: 22 meters long Mega Strong: 20 meters long

LONGOPAC MIDI

Diameter: 465 mm Standard: 85 meters long Strong: 70 meters long Mega Strong: 25 meters long

LONGOPAC MAXI

Diameter: 570 mm Standard: 110 meters long Strong: 90 meters long X-Strong: 70 meters long

STRENGTHS

- Standard Mini, Midi, Maxi
- Strong Mini, Midi, Maxi
- X-Strong Mini, Maxi
- Super Strong Mini
- Mega Strong Mini, Midi

QUALITY

Length and strength measured in Dart Drop is guaranteed. Every roll of Longopac film is Dart Drop tested according to ASTM D-1709. From the reference number, which is printed on every box and on the film, we have traceability all the way to the material batch.

The black odor-control cassette is

an extra airtight bag cassette for

Longopac Stand. With this cassette

you can control odors associated

Dart Drop ASTM D-1709, ISO 7765

Paxxo uses the Impact Resistance of Plastic Film by the Free-Falling Dart Method and guarantees the strength measured in Dart Drop for 2 years.

The most common scientific way to test plastic film is by applying the Dart Drop method. The execution of the method can be seen in its entirety on Paxxo's website: www.paxxo.se/videos/

VERSIONS

Food

This bag cassette is certified by Normpack (Swedish Code for Food Packaging Materials) for the handling of food and pharma. Food can be packaged for re-use and Pharma for bulk handling.

with waste such as diapers.

Odor control

Electro Static Discharge bag cassettes are available in areas that require antistatic material. The surface resistivity value is 1.0E +10 Ohm.

Perforated

This version is only available for Longopac Maxi. The bag cassettes is used for recycling of plastics to enable better result in compactors. There are 6 perforations every 25 cm.

Biodegradable

Bio bag cassettes are available for either the disposal or composting of food waste and other organic waste. The Bio bag cassette is produced of organic material that is certified according to EN 13432:2000-12. The material degrades within 6 months at 23°C / 73°F.

Pacto

The transparent Pacto material is weldable and can be used for closure and sealing to prevent permeation of environmentally hazardous waste and odors.

Sterile

Longopac Mini bag cassettes can be gamma sterilized and are packaged in air tight protective bags.















